

# WHEEL LOADER BLADE

The perfect solution for your bucket of the wheel loader



The new PUCEST Wheel loader blade in Silent quality with excellent characteristics:

- perfect surface cleaning in one stroke
- energy-saving
- surface gentle
- cutting edges on both sides: double useful life as the cutting edge can be easily turned around
- good weather resistance
- good sound insulation

**ON DEMAND ALSO AVAILABLE AS SPARKING REDUCED VERSION  
(INCL. SCREWS):**

- perfect surface cleaning in one stroke
- energy-saving
- surface gentle
- cutting edges on both sides: double useful life as the cutting edge can be easily turned around
- secure usage in biomass- and composting plants: reduced spark formation during skimming process
- good weather resistance
- good sound insulation

Sparking reduced because of aluminum backing material

**ATTENTION:**

Please absolutely ensure that the backing material does not get through during usage!!

**MATERIAL PROPERTIES**

Degree of Hardness	DIN 53 505	ShoreA	55	65	85	TIX
Abrasion	DIN ISO 4649	mm <sup>3</sup>	<b>6,3</b>	<b>6,4</b>	<b>7,6</b>	<b>41,9</b>
Tensile strength	DIN 53 504	N/mm <sup>2</sup>	24,6	43,3	47,7	...
Tear prolongation resistance	DIN ISO 34-1	N/mm	18,7	20,8	25,1	...
Elongation at tear	DIN 53 504	%	623	564	475	225
Rebound Resilience	DIN 53 512	%	50	50	43	...
Temperature range	from -30 ° to 80 °, max. during short time up to 100 °					