

ELEVATOR BOWL ACCORDING TO DIN



- Standard Elevator bowl according to DIN
- Prompt delivery, reasonable prices
- All the models and dimensions are available for shipment (bulged or disk-shaped, no problem)
- An option of improved edges and bevels for covering with hard coating (shear line)

ELEVATOR BOWL WITH FLEXIBLE BOTTOM



- Proper and complete discharging of the bowls through the flexible PUCEST bottom
- Extremely durable and weather-resistant flexible PUCEST bottom
- All the Models and the dimensions available for shipment (bulged or disk-shapes, no problem)
- An option of improved edges and bevels for covering with hard coating (shear line)

MATERIAL PROPERTIES

Degree of Hardness	DIN 53 505	ShoreA	55	65	85	TIX
Abrasion	DIN ISO 4649	mm ³	6,3	6,4	7,6	41,9
Tensile strength	DIN 53 504	N/mm ²	24,6	43,3	47,7	...
Tear prolongation resistance	DIN ISO 34-1	N/mm	18,7	20,8	25,1	...
Elongation at tear	DIN 53 504	%	623	564	475	225
Rebound Resilience	DIN 53 512	%	50	50	43	...
Temperature range	from -30 ° to 80 °, max. during short time up to 100 °					